BIOROLES®



FACE RECOGNITION ACCESS CONTROL SYSTEM

India's Most Trusted, Sold Best in Class, Fully Loaded

SPECIFICATION Product Name : Face Recognition BS-606Ai Screen: 4.3 Inch, HD 272"480, Capacitive Touch Screen Operation system : LINUX 3.10 CPU.NPU: 1.2G Dual-Core ARM Cortex-A7, 600G (0.6T)1GB RAM: 256MB DDR3 **ROM**: eMMC Flash 4GB Binocular camera: 200W Colorful WDR+200W Infrared live camera Face Recognition Accuracy: 99.70% Recognition Distance: 0.5-2.5 meters Working Style : Online Prevent Photo: Dual camera anti-counterfeiting prevents recognition with photo/video USB: USB2.0 x1, Supports U disk import/export data **Power supply :** DC12V interface x 1 Speaker Interface : Reserved for extended Speaker Interface Network Communication : TCP/IP Support C/S LAN communication, USB Free Attendance software : Support exporting excel attendance report with U disk Shift : Support shift setting and importing shift

schedule -U disk

FEATURES

- 4.3 -inch 272"480, Capacitive Touch Screen
- 200W Colorful WDR+200W Infrared live camera
- Adjusts supplement light brightness manually
- Face recognition in a dark environment
- Face recognition distance: 0.5 to 1.5m
- Deep learning algorithm
- 5,000 face capacity 5,000 Card and 5,00,000 Log capacity

RED

- Multiple authentication modes
- Face recognition duration 0.25 seconds
- Stand-alone operation
- Transmits data to the client software via TCP/P Support C/S LAN communication, USB & saves the data on the client software
- Capture linkage and captured pictures saving
- Imports data to the device from the client software
- Manage, search & set device data after logging in to the device locally





靏 +91 8448239993

•-90/9,1st Floor, Okhla Industrial Area, Phase 1, New Delhi-110020