



Face



Fingerprint

FEATURES

- 4.3 -inch 272"480, Capacitive Touch Screen
- 200W Colorful WDR+200W Infrared live camera
- Adjusts supplement light brightness manually
- Face recognition in a dark environment
- Face recognition distance: 0.5 to 1.5m
- Deep learning algorithm
- 5,000 face capacity 10,000 Finger and 5,00,000 Log capacity
- Multiple authentication modes
- Face recognition duration 0.25 seconds
- Stand-alone operation
- Transmits data to the client software via TCP/P Support C/S LAN communication, USB & saves the data on the client software
- Capture linkage and captured pictures saving
- Imports data to the device from the client software
- Manage, search & set device data after logging in to the device locally

Model BS - 607Ai

FACE & FINGER TA & PROFESSIONAL ACCESS CONTROL DEVICE

SPECIFICATION

Product Name : Face & Finger Recognition BS-607Ai

Screen : 4.3 Inch, HD 272"480, Capacitive Touch Screen

Operation system : LINUX 3.10

CPU.NPU : 1.2G Dual-Core ARM Cortex-A7, 600G (0.6T)1GB

RAM : 256MB DDR3

ROM : eMMC Flash 4GB

Binocular camera : 200W Colorful WDR+200W Infrared live camera

Face Recognition Accuracy : 99.70%

Recognition Distance : 0.5-2.5 meters

Working Style : Online

Prevent Photo : Dual camera anti-counterfeiting prevents recognition with photo/video

USB : USB2.0 x1, Supports U disk import/export data

Power supply : DC12V interface x 1

Speaker Interface : Reserved for extended Speaker Interface

Network Communication : TCP/IP Support C/S LAN communication, USB

Free Attendance software : Support exporting excel attendance report with U disk

Shift : Support shift setting and importing shift schedule -U disk



+91 8448239993

www.bioroles.com | info@bioroles.com

F-90/9,1st Floor, Okhla Industrial Area, Phase 1, New Delhi-110020