
BIOROLES®




5 Zone Walk Through Metal Detector BS-27/5

Device Performance

- Digital display on the main control box, providing real-time data on people count, alarm frequency, and detected metal quantities;
- Suitable for a wide range of scenarios, this security gate is perfect for indoor use, ensuring effective metal detection in diverse environments;
- Enjoy hassle-free setup with convenient installation, making it a practical choice for businesses and venues seeking efficient security solutions.

Dimension



Technical Parameters

: BS-DZ5
: 2165 x 828 x349
: 2017 x 720 x 278
: 24kgs
: 30kgs
: 3/5/6/9/11/18 zones
: AC90V~240V 50/60Hz
: 12W
: 1-99 frequency bands
: -20°C~65°C
: 100cm wide * 200cm long (minimum range without metal)
: Maximum sensitivity ≥ 30g metal

BIOROLES®

Technical Standard

Refer to EN60950 safety standard for electrical appliances	Compliance
Radiation shall be implemented according to EN50081-1 standard	Compliance
Refer to EN50082-1 standard for anti-interference	Compliance
The enterprise has passed the IS09001:2008 quality management system certification	•
The enterprise has passed OHSASI 8001 occupational health certification	•
The enterprise has passed ISO14001 environmental management certification	•
The product has passed the EU CE certification	•

Functional Configuration

Portable metal objects can be excluded	0	
Double groups of high brightness red green digital tube display function	•	
Integrated four button panel operation mode	•	
Multiple networking interfaces	1	
External control alarm device port	1	
Secondary development port/upgrade port	1	
Number of Passed statistical function	•	
Statistics of alarm times	•	
Inquire through the number of people	•	
Password protection function	0	
Multi location simultaneous detection and alarm function	1	
Intelligent differentiation function for detection of large items	1	
Super brightness chip intelligent partition alarm indicator	1	
Super brightness patch double row location indicator	/	
100 selectable working frequency bands	•	
Alarm sound mute mode setting	٠	
Alarm sound adjustable mode	•	
Multiple alarm sound selection modes	•	
Front and rear unilateral position alarm indicator switch function	1	
Infrared start/stop function	•	
Front bilateral zone alarm indicator	1	
Front and rear four-sided zone alarm indicators	1	
Adjustable sensitivity for each detection zone	•	
Adjustable sensitivity from 0 to 399 levels in each zone	•	
Safety level 0-99 selectable	•	
Independent 8 probe interactive 1 zone defence	•	
Battery life 2 hours/optional	1	
Battery life 8 hours/optional	1	
A wide selection of quick set-up scenes	•	
Factory reset function	•	

