

Swing Gate OPENER

Open the gate manually by this tool.

- **In case of power failure** : Use the manually spanner to release to separate the motor and gate, open or close the gate manually.
- **When Gate is Obstructed** : Gate stops .
- **Optional** : The Gate Opener Controller can be connected to a solar system, a flash light warning, a photocell, back up battery, keypad and other access control devices.
- **Speed Control** : Gate opening and closing speed can be adjusted.
- **Gentle Start** : The Gate Opener is equipped with a soft start function.
- **Auto Close** : The Gate Opener System is equipped with Auto close function with adjustable closing time delay.
- **Single or Dual Gate** : Either Single or Dual Swing Gate can be opened.
- **Multiple Remote Transmitters** : The Controller can easily accommodate several unique extra remotes to control the swing gate opener

SPECIFICATION

Motor voltage : 24VDC 40W

Rotational speed :200 RPM

Arm's max travel : 300 mm

Max single-leaf length : 2.5meters

Environment Temperature : -45°C ~ +50°C

Max gate open angle : 110 degree

Input power : 220VAC±10%/120VAC±10%

Arm's extended speed : 1.6 cm/s

Continue running time : 5 minutes

Max single-leaf weight : 200 KG

Protection Class : IP55

Dual Swing Gate Gross weight : 15KG



+91 8448239993

www.bioroles.com | info@bioroles.com

F-90/9,1st Floor, Okhla Industrial Area, Phase 1, New Delhi-110020