



## Sliding Gate Operator

**SG0-30**

### Features

- Most economic solution for light duty gate application.
- AC 220V motor with built in control panel (110V version optional).  
Soft start and soft stop
- Metal output gear and enhanced glass fiber nylon internal gear make it durable and silent..
- Resistance sensitivity and auto-closing delay time adjustable.
- Stop/Reverse in case of obstruction during gate opening/closing.
- User friendly dip switch setting makes it simple for DIY application.
- Reliable magnetic limit Switch.
- Manual release key in case of power supply failure.
- 12 months guarantee; lifelong post sales service.



Push Button Input



Safety Beam Ready



Smart Sensitivity






Auto Close



Courtesy light Output

### Dimensions



### Specification

|                          |                            |
|--------------------------|----------------------------|
| Power supply             | : 220V±10%/50Hz            |
| Motor                    | : 220V AC                  |
| Absorbed motor power     | : 130W                     |
| Gate moving speed        | : 12m/min                  |
| Max gate weight          | : 300KG                    |
| Environmental conditions | : -25°C~+50°C              |
| Protection class         | : IP44                     |
| Dimensions               | : 24cmX16cmX27.3cm (L*W*H) |
| Remote control distance  | : 30-50m in the open area  |
| Output gear module       | : M=4                      |
| Output gear number       | : Z=16                     |

